



prestolite®

SERVICE INFORMATION

Governor Advance Data

Distributor

Page 1 of 19

Issued 3/16/78

DISTRIBUTOR GOVERNOR ADVANCE DATA

All test figures shown in the following tabulation are given in distributor RPM's and distributor degrees of advance. Allowable variation is $\pm 1^\circ$ at all points except start, at which point the allowable variation is ± 50 RPM.

Auto. Curve No.	Zero Advance RPM	Intermediate Advance						Full Advance	
		Adv. °	RPM	Adv. °	RPM	Adv. °	RPM	Adv. °	RPM
A	150	4	400	8	800	12	1200	15.5	1400
B	200	3	450	6	650	9	890	12.5	1200
C	200	4	525	8	850	12	1170	15	1400
D	200	4	470	8	735	12	1000	15	1200
E	150	4	550	7	850	11	1250	14.5	1600
F	200	2	400	4	590	6	780	8	1000
G	400	4	800	8	1200	12	1600	16	2000
78	100	4	485	8	875	12	1260	15	1550
81	200	4	470	8	735	12	1000	15	1200
85	240	2	410	5	670	8	930	10	1100
86	200	2	415	5	745	8	1075	11	1400
90	750	1	900	4	1200	7	1500	10	1800
91	160	2	450	5	890	8	1315	10	1600
95	300	2	480	5	740	8	1005	10	1180
100	100	1	300	4	695	7	1050	10	1400
103	250	1	500	3	835	5	1470	5.8	2000
104	200	4	390	8	580	12	770	15	910
105	200	4	485	8	765	12	1045	15	1250
106	100	4	260	8	420	12	580	15	700
107	135	3	230	6	320	9	410	12.5	515
108	100	2	265	5	510	8	760	11	1000
111	160	3	430	6	710	9	980	12	1250
112	200	1	360	2	540	3	755	4	1100
113	250	1	400	4	700	7	1000	10	1300
114	250	4	405	12	690	17	950	21	1400
115	150	4	395	8	630	12	875	15	1050
120	140	2	225	5	350	8	475	11	600
122	225	4	395	8	570	12	745	15	875
123	100	1	200	6	410	11	620	15.2	800
124	100	3	520	6	935	9	1345	11.5	1700
126	100	4	360	8	620	12	880	15	1070
127	200	4	510	8	815	12	1125	15	1350
129	400	1	600	4	930	8	1230	11.75	1700
132	200	2	285	5	415	8	540	10	625
134	200	3.8	400	10	840	16	1250	21	1600
138	200	2	490	4	770	6	1050	8.5	1400
139	300	2	510	4	725	6	940	8	1150
140	200	4	505	8	810	12	1120	15.75	1400
141	200	4	315	9	460	13	575	17.5	700

File in the

L-600 SERVICE MANUAL



Distributor Section