

CHRYSLER 360 • 6.123 ROD • FLAT TOP



BORE	STROKE	COMP HT.	O.E. DECK HT.	LOCKRING	ALLOY
4.000	3.580	1.675	9.599	PRH107-3	HYPEREUTECTIC 390

OVERSIZES: STD, .020, .030, .040, .060, .070*
PIN SIZE / PIN #: 0.9842 / 0984X300K
RINGSET PART#: 4000AM8

NOTES: Centered pin. Piston may protrude on 1992 and up Magnum truck blocks.
 * .070" oversize can be used with 340 block and 360 crank.

PISTON#	PISTON & RINGS	RING PACK	DISH/DOME	COMP RATIO 62cc 64cc 68cc 72cc	GRAM WEIGHT	TOP LAND	INT. VALVE DEPTH/DIA.	EX. RELIEF DEPTH/DIA.
KB107	KB107 KTM	2-5/64, 1-3/16	FT 5cc 2V	10.9 10.7 10.2 9.8	524/132	.274	.280-2.160"	.280-2.160"

CHRYSLER 360 • 6.123 ROD • QUENCH HEAD



BORE	STROKE	COMP HT.	O.E. DECK HT.	LOCKRING	ALLOY
4.000	3.580	1.675	9.599	PRH107-3	HYPEREUTECTIC 390

OVERSIZES: STD, .020, .030, .040, .060
PIN SIZE / PIN #: 0.9842 / 0984X300K
RINGSET PART#: 4000AM8

NOTES: Centered pin. Piston may protrude on 1992 & up Magnum truck blocks. Quench dome elevated .085". Machining required to achieve optimum quench. Will not work with Magnum or Edelbrock closed chamber heads.

PISTON#	PISTON & RINGS	RING PACK	DISH/DOME	COMP RATIO 62cc 64cc 68cc 72cc	GRAM WEIGHT	TOP LAND	INT. VALVE DEPTH/DIA.	EX. RELIEF DEPTH/DIA.
KB373	KB373 KTM	2-5/64, 1-3/16	QH 2.8cc 2V	11.2 11.0 10.5 10.0	522/132	.275	.286-2.200"	.286-2.200"

CHRYSLER 360 • 6.123 ROD • SOLID DOME



BORE	STROKE	COMP HT.	O.E. DECK HT.	LOCKRING	ALLOY
4.000	3.580	1.675	9.599	PRH107-3	HYPEREUTECTIC 390

OVERSIZES: STD, .020, .030, .040, .060
PIN SIZE / PIN #: 0.9842 / 0984X300K
RINGSET PART#: 4000AM8

NOTES: Centered pin. Piston may protrude on 1992 and up Magnum truck blocks.
 Does not fit 62cc Magnum Head.

PISTON#	PISTON & RINGS	RING PACK	DISH/DOME	COMP RATIO 62cc 64cc 68cc 72cc	GRAM WEIGHT	TOP LAND	INT. VALVE DEPTH/DIA.	EX. RELIEF DEPTH/DIA.
KB190	KB190 KTM	2-5/64, 1-3/16	.080" SD -1.2cc 2V	11.8 11.5 10.9 10.5	524/132	.275	.366-2.200"	.366-2.200"
KB191	KB191 KTM	2-5/64, 1-3/16	.200" SD -11.2cc 2V	13.6 13.2 12.5 11.8	559/132	.275	.343-2.200"	.331-1.720"

CHRYSLER 408 • 6.123 ROD • STEP DISH



BORE	STROKE	COMP HT.	O.E. DECK HT.	LOCKRING	ALLOY
4.000	4.000	1.465	9.599	PRH107-3	HYPEREUTECTIC 390

OVERSIZES: STD, .020, .030, .040, .060, .070, *.080
PIN SIZE / PIN #: 0.9842 / 0984X216K
RINGSET PART#: 4000AM8

NOTES: Centered pin. Can be used with Magnum rod, small end narrowed to 1". Made w/Chry 360 block. KB356 use with open chamber heads, has an elevated .085" quench dome.
 *KB416 use with closed chamber heads, no quench dome.

PISTON#	PISTON & RINGS	RING PACK	DISH/DOME	COMP RATIO 62cc 64cc 68cc 72cc	GRAM WEIGHT	TOP LAND	INT. VALVE DEPTH/DIA.	EX. RELIEF DEPTH/DIA.
KB356	KB356 KTM	2-5/64, 1-3/16	QH 23.5cc 2V	9.9 9.7 9.4 9.0	479/132	.275	.286-2.200"	.286-2.200"
*KB416	KB416 KTM	2-5/64, 1-3/16	SDish 25cc 2V	9.8 9.6 9.3 8.9	478/132	.275	.286-2.200"	.286-2.200"